

### SPECIALTHING INTERNATIONAL CO., LTD.

Unit 7, 7/F, Block A, Veristrong Industrial Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, N.T., H.K.

Home Page: http://www.specialthing.com.hk Tel: (852) 2691 7123 Fax: (852) 2606 2324 E-mail Address: info@specialthing.com.hk

## **SPECIFICATION**

# **PROFESSIONAL DIGITAL FM HEADPHONE RADIO** WITH PTL AND AUX IN JACK

	July 3, 2019						
	Jaily 3, 2013						
MODEL NO	HP-53FJBM						
BRAND/TRADE MARK	SPG						
SIZE RANGE	SMALL/MEDIUM/LARGE						
UNIT DIMENSION	198 (L) x 128 (W) x 95 (H) MM						
UNIT PACKAGING	ONE PIECE WITH A BUBBLE BAG IN A PRINTED GIFT BOX						
FEATURES	SUPERB NEW DESIGN						
	ADJUSTABLE AND COMFORTABLE HEADBAND						
	COMFORTABLE EARPADS						
	STATE OF THE ART FM HEADPHONE RADIO						
	DIGITAL TUNE						
	PRESET STATIONS						
	PRESS TO LISTEN FUNCTION     LCD CLOCK DISPLAY						
	LCD CLOCK DISPLAY     LCD EDECLIFICATION						
	<ul> <li>LCD FREQUENCY DISPLAY</li> <li>LOW BATTERY SYMBOL ON THE DISPLAY</li> </ul>						
	EQUIPPED BY SHORT FLEXIBLE ANTENNA						
	STEP-FREE ADJUSTABLE HEAD SIZE SETTING						
	WIDE AND EXTRA SOFT EAR CUSHIONS						
	OPERATED BY TWO "AA" SIZED BATTERIES (NOT INCLUDED)						
	CAN ACT AS A HEARING PROTECTING EQUIPMENT						
APPLICATION	- PROTECTION ON HEARING WHEN WORKING IN NOISY ENVIRONMENT						
	(WHEN OPERATING MACHINERY, LAWN MOWING AND ROAD WORK…)						
	- RECEIVING RADIO BROADCASTING						
	- PROTECTION OF EAR AGAINST COLD ENVIRONMENT						
OPERATING TEMPERATURE	BETWEEN + 50° TO 0°						
CUSHION	PU & FOAM						
EAR CUP	ABS						
MINIMUM SOUND	SNR = 28 dB, H = 29 dB, M = 26 dB, L = 19 dB						
ATTENUATION							



### SPECIALTHING INTERNATIONAL CO., LTD.

Unit 7, 7/F, Block A, Veristrong Industrial Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, N.T., H.K.

Tel: (852) 2691 7123 Home Page: http://www.specialthing.com.hk Fax: (852) 2606 2324 E-mail Address: info@specialthing.com.hk

## **SPECIFICATION**

# PROFESSIONAL DIGITAL FM HEADPHONE RADIO WITH PTL AND AUX IN JACK

### **Technical Data**

Weight (exclude accessories)	Approx. 346 g without batteries				
Operating temperature	Between +50 °C to 0 °C				
Power Supply	2pcs. 1.5V Alkaline Battery				
Frequency Range Radio	FM 87.5 – 108 MHz;				
Frequency Response	20 Hz – 20 kHz				
Impedance	32 Ohm ±10%				
Material in Plastic	ABS				
Material in Ear Cushion	Foam				
Material in Headband Cushion	PU & Foam				
Material in Headband Frame	Metal				
Size Range of the Headband	S, M and L				
Max Sound Level FM Radio	75.8 dB(A)				
Receiver					
Max Sound Audio Input	-14.5 dBm (147mV) for max output level 76.8				
Max Sound Addio Input	dB(A)				

#### **Attenuation Table**

Enganomary (IIIa)	63	125	250	500	1000	2000	4000	8000
Frequency (Hz)	03	123	230	300	1000	2000	4000	8000
Mf (dB)	15.9	17.2	21.9	25.2	31.3	33.8	35.6	36.6
Sf (dB)	3.5	3.4	3.6	2.2	2.4	3.4	2.8	5.2
APV (dB)	12.4	13.8	18.3	23.0	28.9	30.4	32.8	31.4

SNR = 29 dB H-value = 31 dB M-value = 26 dB L-value = 20 dB

### **Level Dependence**

Criterion Level H = 109.6 dB M = 106.8 dBL = 94.9 dB

### Notes

- Certain chemical substances may adversely affect this product. Further information should be sought from the manufacturer, importer or distributor;
- When hygiene covers are put on to the cushions, it may affect the acoustic performance of the earmuffs;
- Do not tear the cushion off from the headset, as the cushion is non-replaceable;
- Earmuffs, and in particular the cushions, may deteriorate with use and should be examined frequently for cracks and leakage;
- The product is protected by bubble wrap and then put into a printed gift box. After use, put it back into to the gift box for storage.